

8000

Rol

Franklin

Section Line 200 S OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION \_\_\_12 \_\_TOWNSHIP\_ 15 RANGE\_ DATE: \_\_\_\_7-21-99--6-5-04 Wilcoxen PARTY CHIEF:\_\_\_ CREW: \_ TYPE OF MARKER: Harrison METHOD OF ESTABLISHMENT: County: IN. S.P.C. E ZONE, NAD 83 NAME: 15041203 N: 501918,2134(m) E١ 69192.6628(m) 2. 39,38, 105.05' Section Line 200 S 5. 8000 Ro Franklin

Original post set 1820 by John Hendricks with witnesses: 14" beech N 89 W 15 links, 6" sugar S 85 E 9 links per Marion County Atlas pg. 10. A survey by D.W. Voorhis on June 10, 1868 indicates no stone or witnesses per Warren Township Legal Survey Book pg. 46. Wilcoxen 4-12-76 called a PK nail. Jacobs 10-20-88 called a PK nail. Whiteside 7-31-96 called the same. Excavated by Wilcoxen 7-22-99 and PK nail was found 3" down as per ties. Harrison set.

1.1	~	_	4	4	2	^	-	
H	L	Э	4	1	C	U	ರ	

REF.	DISTANCE	DESCRIPTION
1.	161.72'	Due N to NW 7-15-5
2.	99.98'	Top nut of fire hydrant
3.	143.19'	PK nat E PwP#43-549 2'up Mag nail w/brass washer E
4.	37.55'	Cut 'x' in curb
5.	105.05'	SE corner of ADDRESS 234 "Just Add Water"
6.	54.22'	PK nail E PwP#44-549 (in grass island)
7.	145.27	Mag nail w/bw W guide pole #89-550 6"up
	]]	BU THE STATE OF TH